

XR15-W Wheel Drive

Ultra-Low Profile, Direct-Drive, Brushless Wheel Motor

XR15-W Comprising ...

- External/Outer Rotor DC Brushless Motor Design
- Integrated High Resolution Encoder
- High-Capacity Bearing
- Simple Integration via Direct-Mount to Vehicle Platform
- Easy-Fit for Customer Tyre



PMW Dynamics Limited

Newman Lane | Alton | Hampshire | GU34 2QW | United Kingdom

T: +44 (0) 1420 594 140 | E: sales@pmwdynamics.com | W: pmwdynamics.com

© PMW Dynamics Limited 2023

Provisional Datasheet. Contents subject to change without notice. Please contact PMW Dynamics to confirm specific performance and/or physical properties that are critical for your application

Performance Data

Performance Data		
Motor Rated Torque	8.0	Nm
Motor Rated Speed	580	RPM
Motor Rated Power	486	W
Motor Peak Torque	13.0	Nm
Speed at Peak Torque	460	RPM
Electrical Data		
Motor Rated Voltage	42.0	VDC
Motor Rated Current	12.0	A _{RMS}
Motor Torque Constant K _t (±10%)	0.56	Nm/A _{RMS}
Motor Velocity Constant K _e (±10%)	0.56	Vs/rad
Motor Pole Pairs	8	
Encoder Resolution	4,096 Differential Output	PPR
Integrated Thermal Sensor	10KΩ NTC	
Mechanical Data		
Overall Mass	2.65	kg
Max. Axial Load (@120mm PCD)	1,000	N
Max. Radial Load	650	N
Max. Moment Load	TBA	Nm
Environmental Data		
Operating Temperature	-10°C to +40°C	
IP Rating	IP54	

Provisional Datasheet:

Contents subject to change without notice. Please contact PMW Dynamics to confirm specific performance and/or physical properties that are critical for your application

Outline Drawing High Performance XR15-W

